

R Series

Efficiently logging sales transactions in your system becomes imperative as waiting lines expand. Therefore, possessing software that expedites product scanning and sales processes, minimizing time wastage, proves highly advantageous for a retail business



R Series Variants

Basic



Standard



Advanced



intel Core

i3

intel Core

i5



DDR III

DDR3L / DDR3 1600MHz
PC3L-12800 / PC3-12800
Non-ECC Unbuffered
1.35V / 1.5V CL11 2Rx8
Dual Rank 204 Pin SODIMM



SSD mSATA

Interface: mSATA III (6.0 Gbps)
Dimension: 1.18in X 1.96in X
0.14in / 30mm X 50mm X 3.5mm
Read/write speed: 500MB/s, 240MB/s



Display

Diagonal Screen 15.6"
Max Resolution 1366 x 768
Aspect Ratio 9:6
Color Support 16.7 Million Colors
Image Brightness 460 nits
Image Contrast Ratio 400:1



Power

Input: 110V-240V
50/63Hz 2A
Output: 12V DC 8A
96W MAX



USB 3.0

Data Rate Speed 4.8Gbps
4 wires: SuperSpeed
3 wires: Vbus/GNDx2
2 wires: DP/DM for USB 2.0 2
Supply to Bus Max. 900 mA



VGA

Connector: DE-15
Pins: 15
Refresh rate: 60 Hz hp.com
Video signal: RGB video
signal plus option
H and V sync
Data signal: I²C data channel
for DDC information



Ethernet

RJ45, Single Port, 1 x 1
RJ Type Jacks & Plugs
Jack, Shielded
Cat 5, Inverted - Latch Up
LED Status Indicator
8 Position
Speed 10/100/1000Mbps



Audio

Pin: 3.5mm
Audio & Mic